THE BEST & STRONG "ACCELERATOR "

CAIRAN MEMPERCEPAT KERING MORTAR

THE BEST & STRONG

Accelerator

Set Accelerating Admixture

Description A concentrated solution of accelerating, plasticizing, and shrinkage - reducing agents. It is added to Portland cement to produce quick setting mortar.

Use To produce quick setting, low shrinkage, high strength concrete patches.

It can be used for sealing leakages and for plugging water infiltrations in concrete.

Advantages

- Rapid set time
- Low shrinkage
- ☐ Good adhesion
- ☐ High early strength & compressive strength.

Dosage Added to the mixing water within the range 1:0-1

Instructions for Use

Surface Preparation

Chip away deteriorated, unsound substrate Clean cavity completely.

Mixing The Best & Strong is to be used with fresh Portland cement.

Actual initial and final setting time will vary with different brands of cement and job conditions, test with small quantities of cement to be used should be conducted on job site to determine proper dilution ratio for the desired setting time.

Application As Waterplug

Plug cement paste into crack or hole. Hold in place with hand, until it has hardened.

As Dry Pack Mortar

Used for patching concrete structures. Dry pack mortar is made with 1 part OPC + 2 sand + The Best & Strong accelerator diluted with 2 to 5 parts water, depending on setting time desired.

Technical Data

Form Clear liquid

Specific Gravity Approx. 1.28 kg/ltr Storage Dry, cool, shaded place Shelf Life 1 years when unopened

Packaging 200 kg drum

20 kg can

Handling Precautions:

- ☐ Avoid contact with skin and eyes
- ☐ Wear protective gloves and eye protection during work
- ☐ If skin contact occurs, wash skin thoroughly.
- ☐ If in eyes, hold eyes open, flood with warm water and seek medical attention without delay

Distributed: CV. ANUGERAH – WATERPROOF Telp:031-7670735 Fax: 031-7672945